

OSHA-Required Health And Safety Information!

This Material Safety Data Sheet (MSDS) was requested moments ago from Hercules Automated Fax Information System. Please forward it immediately to the person in charge of MSDS's, or retain it at the machine until claimed.

Section 1

MATERIAL SAFETY DATA SHEET # 37 Flip Stick®

Date Prepared: 1/31/1990 Last Reviewed: 12/4/2002

Meets OSHA 29 CFR 1910.1200

MATERIAL SAFETY INFORMATION SERVICE

Hercules Chemical Company Inc. 111 South Street Passaic NJ 07055 Phone (800) 221-9330 Fax (800) 333-3456

Section 2 - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;

Common Name(s), CAS Numbers)

OSHA PEL

ACGIH TLV

Other Limits

Upper Bound Limit if SARA Reportable

Cupric Chloride (1344-67-8)

N/A

1mg/M³(dust)

1mg/M³

10%

HMIS Hazard Rating: Health: 2 Flammability: 0 Reactivity: 0 Personal Protection: E

Section 3 - Physical/Chemical Characteristics

Boiling Point (°C):

Specific Gravity (H2O = 1): Vapor Density (Air = 1): Vapor Pressure (mm Hg):

N/A

0.95 to 1.0

N/A

N/A

UEL:

LEL:

Melting Point (° F)

Evaporation Rate: (Butyl Acetate = 1) Solubility in Water:

N/A

Partially

Appearance And Color:

Bluish green crystalline powder

Odor: No odor

Flammable Limits:

Section 4 - Fire And Explosion Hazard Data

Flash Point:

n Hazard Data

N/A

N/A

•••

Extinguishing Media: Water, fog, dry chemical, carbon dioxide.

Special Firefighting Procedures:

This product has combustible materials and supplies its own oxygen for sustaining the combustion.

Unusual Fire And Explosion Hazards:

None

Continued on Next Page

Section 5 - Reactivity Data

Stability: Stable Conditions To Avoid: None

Incompatability N/A

(Materials To Avoid):

Hazardous Decomposition: None

Hazardous Polymerization: Will Not Occur

Section 6 - Health Hazard Data

Routes of Entry: Inhalation YES/Primary Skin YES/Primary Ingestion YES/Secondary

Health Hazards:

Inhalation of heavy dust may irritate nose and throat. Ingestion can cause injury to mouth.

Carcinogenicity: NTP NO IARC NO OSHA Regulated NO

Signs And Symptoms of Exposure:

Irritation of nose and throat. Irritation of eyes and possible conjunctivitis.

Medical Conditions Generally Aggravated By Exposure:

None

Emergency And First Aid Procedures:

EYES: Immediately flush with large amounts of water for at least 15 minutes. If irritation persists, obtain medical attention. SKIN: Wash with soap and water. If irritation persist, obtain medical attention. INHALATION: Remove from exposure. If breathing is difficult or discomfort persists, obtain medical attention. INGESTION: Rinse mouth with water. Give water to dissolve particles. Obtain medical attention.

Continued on Next Page

Section 7 - Precautions For Safe Handling And Use:

Steps To Be Taken In Case Material Is Released Or Spilled:

Sweep up the spilled material making sure no dust is created. Avoid flushing to sewer or stream.

Waste Disposal Method:

Non-hazardous landfill

Precautions To Be Taken In Handling And Storing:

Store in cool dry place.

Other Precautions:

None

Section 8 - Control Measures:

Respiratory Protection:

Use NIOSH/MSHA approved respiratory protection if airborne dust is expected

Ventilation: Local Exhaust Adequate

Special N/A

Mechanical N/A

Gloves: None normally required.

Other: N/A

Eye Protection:

Safety glasses if possibility of eye contact with

Other Protective

Clothing: None normally required

Work/Hygienic Practices Use good personal hygiene practices. Wash thoroughly after handling.





For Hercules Material Safety Data Sheets by fax anytime, day or night, just call 1-800-942-INFO (1-800-942-4636) from any Touch-Tone phone. Have your fax number ready. Checking the product label for the correct MSDS # will save time.